DOE Distributed Power & Industrial DG Quarterly Review Meeting

Increasing the Use of DG in the Semiconductor Industry


Subcontract # 400006029







Barry Cummings, SRP



Acknowledgement

- **♯**Joe Galdo, DOE/OPT Program Manager
- **♯**Tom Rizy, Technical Project Monitor Oak Ridge National Laboratory
- **♯**Phil Sarikas, Industry Advisor Intel Corporation





Status

- #Final Report Draft Complete
- #Peer Review in-process

Objectives

- # Management decision guideline
- Research tool for site-specific, feasibility studies
- # Estimated USA DER FAB market

Scope

- **♯** Focus on large 10 to 50 MW semiconductor FAB plants
- # Evaluate economic, reliability, availability, and environmental issues and opportunities
- Evaluate potential multiple uses of DER to justify the investment

Final Report Outline

- # Guidelines for Selecting a DER Project
- **♯** Environmental, Legal, and Institutional Issues
- **■** Design Concepts
- **■** Potential Market Impact
- **■** Risk Assessment
- **#** Conclusions/Results

Appendices

- **♯** Process Diagrams
- **■** Electrical Single Line Diagrams
- **♯** General Arrangements
- **#** Schedules


Conclusions

- **♯** Combustion Turbine only acceptable DER alternative
- **■** By 2010, Fuel cells <u>may</u> acceptable.
- **♯** DER market penetration likely to be limited
- # "Retrofit" existing FABS unlikely to occur
- **★** Except fuel prices, risk will <u>not</u> be a major deterrent


Two alternatives: One GE LM 6000 or Two GE LM 2500

| | CASE | | | | | | | |
|-------------------------------|------|----|-----------------------------|-----|----|----------|---|----|
| | 2A | 2B | 3A | 3B | 4A | 4B | 5A | 5B |
| 1-GE LM 6000 | X | X | X | X | - | | | |
| 2-GE LM 2500 | | | 7,-7 | | X | X | X | X |
| Cogeneration | X | X | X | X | X | X | X | X |
| Combined Cycle | X | X | | | X | X | | |
| Simple Cycle | | | X | X | | | X | X |
| Steam Turbine Chillers | X | 4 | X | 7.4 | X | <u> </u> | X | |
| Absorption Chillers | | X | $\overline{\Sigma}(\Sigma)$ | X | | X | $\langle \hat{\omega} \rangle / \gamma$ | X |

Gas Price versus Electric Prices



Sources of Costs and Benefits




Economic Case Study Example

| | Base Case | Combustion Turbine |
|-------------------------------|--------------|-----------------------|
| Total Capital Cost | \$65 million | \$100 million |
| Net Present Value | Base | \$15 million |
| Simple Payback | Base | 4.0 years |
| Internal Rate of Return (IRR) | Base | 28% |

Economic Assumptions


| Variable | Value | | |
|---------------------------|----------------|--|--|
| Cost of capital | 18% | | |
| Plant life | 15 years | | |
| Grid supplied electricity | \$0.055 / kWH | | |
| Natural gas | \$3.50 / MMBTU | | |
| Excess electricity sales | \$0.05 / kWH | | |

Combustion Turbine effect on PQ sag event



Calculated MTTF as a function of various supply scenarios


(base case = three 69kV sources, no DG)




External Risk Conclusions

- ➡ Siting requirements for space and visual impact only be available at new FAB
- Public process and design alternatives likely to be successful
- Inspections and existing review processes will be challenge
- ★ Size and emission levels unlikely a 'major source' issue.


Capital cost differences




Energy annual cost differences



O&M annual cost differences





Forecast FABs by Wafer Size

| | YEAR | | | |
|------------|------|------|------|--|
| Wafer Size | 2001 | 2002 | 2003 | |
| 6 inches | 2 | 2 | | |
| 8 inches | | 2 | 0 | |
| 12 inches | 2 | 2 | 5 | |
| Total | 5 | 6 | 6 | |

Marker Penetration Conclusion

Market Global Impact Minimal

♯ Number of DERs

★Air emission

♯ Natural gas usage

NOTE: Site specific impacts may be significant